

basic data

Weight category			E	
weight	no handle		295,0 g	
volume to rim			11,70	
top load performance		1	36,0 kg	

dimensions

D1	287,0 x 248,0 mm/inch
D2	270,0 x 230,0 mm/inch
D3	250,0 x 210,0 mm/inch
H without lid	215.0 mm/inch

tolerances


dimensions	±1 mm/in
Weight tolerance	± 5 %

Possible combinations

handle	Description	We	eight	
	plastic handle	20),0 g	
lid	Туре	Description	stacking height two fold	l: each further:
	standard	DETQ 105 P	414,0 mm/inch	198,0 mm/inch
	sealing lid	FDETQ 105 P	437,6 mm/inch	215,7 mm/inch
decoration	Method of decoration	height:	width:	median breadth:
	Digital	145,0 mm/inch	870,0 mm/inch	0,0 mm/inch
	IML	187,30 mm/inch	882,50 mm/inch	
	Offset	145,0 mm/inch	855,0 mm/inch	870,0 mm/inch

Logistics (standard view)

Pallet	EUP (Europallet)
Width	80 cm (31,5´´)
Length	120 cm (47,24´´)
Height	2,00 m
Quantity per pallet	672
Quantity per layer	12



material

Description	Labelling	Recyclingcode

100% Virgin material









misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.





basic data dimensions

Weight category	Е	Dì	283,0 x 243,0 mm/inch
weight	76,0 g	Н	19,0 mm/inch
displaced volume	1,00		

tolerances

dimensions	±1 mm/in
Weight tolerance	± 5 %


Possible combinations

bucket

JSP 36090	JETQ 80 P	JETQ 105 P	JETQ 115 P	JETQ 120 P
756	727	727		721

decoration	Method of decoration	height:	width:
	IML	206,89 mm/inch	246,89 mm/inch
	Offset	0.0 mm/inch	

Logistics (standard view)



material

Description	Labelling	Recyclingcode	
100% Virgin material		^	







misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.





basic data

dimensions

tolerances

Weight category	Е
weight	69,0 g
displaced volume	0,00

Dì	282,0 x 242,0 mm/inch
Н	19,6 mm/inch

dimensions ±1 mm/in/ Weight tolerance ±5 %

Possible combinations


bucket



decoration	Method of decoration	height:	width:
	IML	250,00 mm/inch	210,00 mm/inch
	Offset	0.0 mm/inch	

Logistics (standard view)

Pallet	EUP (Europallet)
Width	80 cm (31,5´´)
Length	120 cm (47,24´´)
Height	2,20 m
Quantity per pallet	3120
Quantity per layer	12



material

100% Virgin material









misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.