



Technical data sheet bucket | JETR 42 P - Jokey Euro Tainer rectangular Profi



basic data

Weight category	E
weight no handle	147,0 g
volume to rim	4,90 l
top load performance	¹ 26,0 kg

dimensions

D1	286,0 x 198,0 mm/inch
D2	272,0 x 184,0 mm/inch
D3	256,0 x 168,0 mm/inch
H without lid	119,0 mm/inch

tolerances

dimensions	± 1 mm/inch
Weight tolerance	± 5 %

Possible combinations


handle	Description	weight
	metal handle	28,0 g
	plastic handle	15,0 g
	roller grips	3,0 g

lid	Type	Description	stacking height two fold:	each further:
	standard	DETR 80 P	230,0 mm/inch	109,0 mm/inch
	sealing lid	FDETR 80 P	248,0 mm/inch	121,0 mm/inch

decoration	Method of decoration	height:	width:	median breadth:
	Digital	70,0 mm/inch	806,0 mm/inch	0,0 mm/inch
	IML	100,68 mm/inch	802,50 mm/inch	
	Offset	70,0 mm/inch	735,0 mm/inch	806,0 mm/inch

Logistics (standard view)

Pallet	EUP (Europallet)
Width	80 cm (31,5´´)
Length	120 cm (47,24´´)
Height	2,20 m
Quantity per pallet	1280
Quantity per layer	16



material

Description	Labelling	Recyclingcode
100% Virgin material		



misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.



basic data

Weight category	F
weight	64,0 g
displaced volume	0,40 l

dimensions

D1	283,6 x 195,6 mm/inch
H	12,8 mm/inch

tolerances

dimensions	± 1 mm/inch
Weight tolerance	± 5 %

Possible combinations

bucket




decoration

Method of decoration	height:	width:
IML	269,00 mm/inch	179,50 mm/inch
Offset	140,0 mm/inch	230,0 mm/inch

Logistics (standard view)

Pallet	EUP (Europallet)
Width	80 cm (31,5´´)
Length	120 cm (47,24´´)
Height	2,20 m
Quantity per pallet	4480
Quantity per layer	16



material

Description	Labelling	Recyclingcode
100% Virgin material		



misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.



basic data

Weight category	E
weight	66,0 g
displaced volume	0,00 l

dimensions

D1	283,0 x 195,0 mm/inch
H	18,8 mm/inch

tolerances

dimensions	± 1 mm/inch
Weight tolerance	± 5 %

Possible combinations

bucket




decoration

Method of decoration	Diameter
IML	0,00 mm/inch
Offset	0,0 mm/inch

Logistics (standard view)

Pallet	EUP (Europallet)
Width	80 cm (31,5´´)
Length	120 cm (47,24´´)
Height	2,20 m
Quantity per pallet	5280
Quantity per layer	16



material

Description	Labelling	Recyclingcode
100% Virgin material		



misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.