4310

1000 ml Packo



| Product part | Product code | Materials |
|-----------------|--------------|-----------|
| Packo container | 4310 | HDPE |

| Capacity | ML | US Fluid ounces |
|-------------|------|-----------------|
| Brimful | 1080 | 36.52 |
| When closed | 1030 | 34.83 |

| Hazardous material information | |
|--------------------------------|---|
| Hazardous material type | Solids |
| Packaging group | 1 – 11 – 111 |
| UN marking | 1H2/X1.3/Y2.0/Z3.0/S//NL/ CURTEC-110503 |
| Maximum gross mass (kg) | X=1.3 Y=2.0 Z=3.0 |



| Weight | Grams | Ounces |
|-----------------|-------|--------|
| Packo container | 72.0 | 2.54 |

Weight tolerance

All products have a tolerance of ±4% of the initial weight mentioned on this data sheet

| Dimensi | ional to | olerand | ce (mm | n) acco | rding t | o DIN1 | 6742- | TG7 | | | | | | | | |
|---------|----------|---------|--------|---------|---------|--------|-------|------|------|------|------|------|------|------|------|------|
| Over | 1 | >3 | >6 | >10 | >18 | >30 | >50 | >80 | >120 | >180 | >250 | >315 | >400 | >500 | >630 | >800 |
| up to | 3 | 6 | 10 | 18 | 30 | 50 | 80 | 120 | 180 | 250 | 315 | 400 | 500 | 630 | 800 | 1000 |
| NW (±) | 0.20 | 0.29 | 0.35 | 0.42 | 0.50 | 0.60 | 0.90 | 1.25 | 1.45 | 1.60 | 1.80 | 2.60 | 3.50 | 4.00 | 4.50 | 5.00 |

| Standard color(s) | Color code | PMS references |
|-------------------|------------|----------------|
| Packo container* | White 004 | / |

* Other colors available on request

| Product identification | |
|------------------------------|--------|
| Manufacturer ID | Bottom |
| Product code | Bottom |
| Recycle logo / Material type | Bottom |
| Date clock | Bottom |
| UN-mark | Bottom |
| Food logo | Bottom |
| Material track clock | Bottom |
| CFR49-mark | |

| Other information | |
|---|--|
| he container can be opened and closed with just a quarter-turn | |
| Il compatible lids are equipped with integrated tear-off tamper evident seal | |
| /laximum filling temperature is 70°C/ 158°F | |
| ontents must have cooled to 30°C/ 86°F before containers can be closed and stacked | |
| oC available on request | |
| IN certificate available on request | |
| /VTR declaration available on request | |
| eak tightness declaration available on request (valid in combination with the 4371 lid) | |
| lser manual available on request | |

DISCLAIMER

CurTec manufactures packaging material for a wide range of purposes. This declaration is restricted to the packaging material as it leaves the production facility. CurTec has neither control over final end use of the product nor over processing conditions. It is therefore the responsibility of the end user to check compliance with the relevant regulations and to validate material performance in the end application through proper end use testing.

© 2021 Property of CurTec International B.V. All rights explicitly reserved, it is not allowed to copy or communicate to other parties without written consent of CurTec.



